




S86

STP

2010-06-18





敏銳 把握應用趨勢

www.ruijie.com.cn



敏銳 把握應用趨勢 · 快捷 滿足客戶需求



1. C3750 C2950 H3C3600 PVST+ C6509 C4507
HSRP PVST+ VTP SNMP
OSPF
2. GDHG NLB
- NLB
- 3



1 MSTP

```

S8610 Catalyst 4507
MSTP S8610 10.3 5 Catalyst 4507
12.2(31)
Catalyst 3700 S8610 Catalyst 4507

1
Catalyst 3700 S8610 4507
8610

2
Catalyst 3700 S8610 3700
4507 3700 8610
3700 8610
3700 4507

37 29 IOS 10.1 10.2

```

2 S8600 H3C 3600 BPDU

```

S8610 H3C 3600 BPDU

H3C 3600 S8610 DISC

H3C 3600 LOG BPDU LOG
%May 20 21:16:01:118 2010 Hostname_H3C3600
MSTP/3/BPDUFORMATCONFIGERROR:- 1 -Port GigabitEthernet1/1/3 received different

```



1.

1)MSTP

2)S8600 H3C 3600 BPDU

MSTP	domain name	revision	instance
	IST 0		2950

CISCO STP	CISCO
STP MSTP	
H3C3600 STP	


1.	2.	3.
4. log	5. show	6. 7.

2.

12.1(22)EA13 MSTP

2950 IOS







C2950 BLOCK
BPDU 802.1s 20002 IEEE Standards for Local and
metropolitan area networks Virtual Bridged Local Area Networks—Amendment 3:
Multiple Spanning Trees

H3C3600

