





# Contents

AP

AC show ap-config summary AP

```
WS18000-1B11#show ap-config summary
Online AP number: 33
Offline AP number: 156

IP Address      Mac Address      Radio      AP Name
-----
00  9:16:34:19 Run  196LE_fangjian_mid_AP/40-1 192.18.37.219 3869.6r34.b2cc 1 E 4 1.1 80 2 E 0 157 1
```

第三频

AC show ac-config client

```
WS18000-1B11#show ac-config client | in mu
===== show sta status =====
AP : ap name/radio id
State: Stand/Power Save/Work Mode/Beaming State/MU-MIMO E-Enable/Power Save-D-Disable/Power Save
TotalSta.Num: 39
STA MAC      IPV4 Address      AP      wlan vlan status      Asso-Auth      Net Auth      Up time
-----
F48b.32a3.04e3      temp/2      6 1731 9.0M/E/ac/R/mu MAB      WEB      0:20:37:33
WS18000-1B11#
```

mu终端



AP Web

WAN



# Contents

AP730(TR) AT

AP730(TR)

## FAQ

Q AP730(TR)5G MU

A 2 1.2

Q AP730(TR) 2 MU

A 5G 4 mu

Q: AP730(TR) LAN2

A LAN2

Q: AP730(TR)

A: AP730(TR) AF AT

Q: AP730(TR) 5G 2

A: 600Mbps+

Q:AP730(TR) ip

A:

Q AP730(TR)LAN2

AP

A:

Q:AP730(TR)

A

, 2G+5G+5G

Q:AP730(TR) LAN

[www.ruijie.com.cn](http://www.ruijie.com.cn)

[www.ruijie.com.cn/service.aspx](http://www.ruijie.com.cn/service.aspx)

