

Ń

copyright © 2024 iHà

Ń

Ń

Ń

o•

o•

yŃ iHà

Ń

Ń

Ń

Ń

Ń

Ⓜ

î æ ð

z ðVid

z ðt

z ð

Ⓜ

z iHð <https://www.ruijie.com.cn>

z iHð <https://www.ruijie.com.cn/fw/>

z iH:ð <https://wind.ruijie.com.cn/>

z iHð 7*24hðUy <https://ocs.ruijie.com.cn>

z iHð 7*24hð 4008-111-000

z iHððÀ 4i:ð <https://www.ruijie.com.cn/special/fw/tool/xryf/>

z iHð Fð ð 4008111000@ruijie.com.cn

z iHð4Fð doc@ruijie.com.cn

iHð-

iHðZ

4i:ð APP

iH:ðZ

7,

1. R

ðð

👍 /(~be7â
/(~be7â*D>

2. y

👍
👍

D

ù ¢

ù ^	1
1 DP	1
1.1 xž	1
1.2		

©Y	Q/L	yf
8	81	N88 • 10M/100M/1000M8
9	VGANM	Nu4 VGANMP888
10	HDMINM	Nu4 HDMINMP888
11	NM	N8 ACz
12	M	8 DB9MkNg*8 z

1.3 CP

 B*D

A 873pG5E8-bCB8B-8-pü >

= 1-3 RG-CT7529 8 CP

C54	RG-CT7529
D	8
R	RG-CT7529
CPU	C86 33508 88 3.0GHz
Ä	8 1*8GB DDR4 UDIMM 2666MHzCY 8y 4*16GB DDR4 UDIMM 2666MHzCY
8	8 1*256GB M.2 NVMe SSD 8y 1*1TB M.2 NVMe SSD 1*1TB M.2 SATA SSD 1*2TB 2.56 SATA 3.0 8 1*2TB 3.56 SATA 3.0 8
R	RG-CT7529
M	1 ACM 2 3.5mm88 /8 2 3.5mm88 /8 1 3.5mm88

	2 10M/100M/1000M 1 Type-CNM 8 USB3.0NM 2 USB2.0NM 1 VGANM 1 HDMINM 2M
%pĚ	N RAINOSgiHĚhu4
Wi-FiNM	u4
RĪ	u4
≠	RG-CT7529
Ě	ĥ
DĚg! xĥ xĥ	290mmx92mmx343mm
DĚMO	4.6kg
ÿ MO	5.8kg
%g	u4
Ě	RG-CT7529
›	Ä 1 ATX›
ÿ	u4Ag AChÿ S ĥy 220V ACk 50Hz S ĥ 3A
Ě	90W
ĚĚi	RG-CT7529
†	WĚ 0°C½ 40°C Ě -40°C½ 70°C ĥ# 3000~5000ĥ# 220kĥ 1-ož
†	WĚ 10%RH~90%RHg(Ě Ě 5%RH~90%RHg(Ě
#	W#y 0m~5000m
‹	RG-CT7529

3 G±

3.1 2

30 : 2 : 2

3-1 2



⚠ #E

B-.2 Ç 4p%ÐOÂOx Fw(ÿ

ç 3-2 Ÿ


3.2 Ÿ

Ÿ

VGAgã HDMIhCjŸ Vµ : Ÿ NM kw1Ÿ

ç 3-

3.3

7      y :

 B*D

Ñ 4.082160.

z

Ñ • 9²

5